



Segrate, 26/03/2018

Based on the data supplied by the builder, Osculati Spa certifies that the item:

STAINLESS STEEL WIRE ROPE INOX AISI316
Features are following listed in the table below as follow

Part number	Construcion	Diameter (mm)	Actual Measurement Diameter (mm)	Tensile strength Mpa		Breaking strength (KN)	
				Standard	Actual measurement	Standard	Actual measurement
03.171.10	1X19	10	10,1	1570	1570	≥82.4	83,2
03.171.12	1X19	12	12,2	1570	1570	≥118.7	119,6
03.171.15	1X19	1,5	1,52	1570	1570	≥1.85	2,04
13.171.20	1X19	2	2,03	1570	1570	≥3.30	3,56
03.171.25	1X19	2,5	2,52	1570	1570	≥5.15	5,45
03.171.30	1X19	3	3,03	1570	1570	≥7.42	7..69
03.171.40	1X19	4	4,05	1570	1570	≥13.19	14,52
03.171.50	1X19	5	5,05	1570	1570	≥20.61	21,42
.03.171.60	1X19	6	6,08	1570	1570	≥29.67	30,65
03.171.70	1X19	7	7,1	1570	1570	≥40.39	41,98
03.171.80	1X19	8	8,1	1570	1570	≥52.75	53,69

(Standards) : All wire comply with the requirements of EN12385

